



STARTING PRESSURE

1,5 bar
2,2 bar



garanzia 1 anno - 1 year warranty

Regolatore elettronico di pressione per elettropompe
Automatic pump control

cod.		pz. x conf.	euro cad.
1600001500	1,5 bar	1	44,500
1600002200	2,2 bar	1	44,500

DATI TECNICI - SPECIFICATIONS

tensione alimentazione monofase 230 V- ± 10%
rated voltage 220-240 V

frequenza 50-60 Hz
frequency 50-60 Hz

indice di protezione IP65
protection rating IP65

intensità Max 10A corrente
intensity Max 10A

pressione massima di esercizio 10 bar
maximum working pressure 10 bar

attacchi 1" maschio
connections 1" male

temperatura massima di esercizio 60°C
maximum temperature rating 60°C

PROTEGGE LA POMPA DA EVENTUALI MALFUNZIONAMENTI O MANCANZA DI ACQUA
SOSTITUISCE IL TRADIZIONALE UTILIZZO DEL VASO DI ESPANSIONE
GESTISCE IL FUNZIONAMENTO DELLA POMPA REGOLANDO LA PRESSIONE
INGOMBRI RIDOTTI - AFFIDABILITA' - SEMPLICE INSTALLAZIONE

PROTECTS THE PUMP FROM ANY MALFUNCTIONS OR LACK OF WATER
REPLACES THE TRADITIONAL USE OF THE EXPANSION TANK
MANAGES THE OPERATION OF THE PUMP BY ADJUSTING THE PRESSURE
REDUCED DIMENSIONS - RELIABILITY - EASY INSTALLATION



	cod.	misura	pz. x conf.	euro cad.
Membrana in para nera per vasi ad espansione da 24 lt.	7000000000	flangia ø 90	30	5,739
	7000000080	flangia ø 80	30	5,582

Black natural rubber membranes for expansion tank of 24 lt