




	cod.	misura	pz. x conf.	euro cad.
<b>Gomito in ottone maschio - maschio</b>	50290TTMMD	1/2" pass.int. ø 13	10	3,200
Brass MM elbow	50290TTMMF	3/4" pass.int. ø 19	10	3,600



	cod.	misura	pz. x conf.	euro cad.
<b>Gomito in ottone maschio - femmina</b>	50290TTMFD	MF 1/2" pass.int. ø 13	10	3,500
Brass MF elbow				



	cod.	misura	pz. x conf.	euro cad.
<b>Rubinetto in ottone sbiancato per gas</b>	1500NTMDD	MM 1/2" x 1/2"	20	13,400
Nichel plated valve for gas	1500NTMFDD	MF 1/2" x 1/2"	20	13,400



	cod.	misura	pz. x conf.	euro cad.
<b>Rubinetto in ottone sbiancato per gas con girello</b>	1500NTGMDD	MF 1/2" x 1/2"	20	14,400
Roating nickel plated valve for gas	1500NTGFDD	FF 1/2" x 1/2"	20	14,400



	cod.	pz. x conf.	euro cad.
<b>Giunto in ottone cromato con adattatori in gomma per gas metano o liquido</b>	5029G00000	10	9,300

Chrome plated brass connection with rubber adapters for natural or liquid gas